




Kalstein®

A different accompaniment, at your service

All rights reserved © KALSTEIN France S. A. S.,

LABORATORY LINES

REFRIGERATORS AND
FREEZERS



All rights reserved © KALSTEIN France S. A. S.,
2 Rue Jean Lantier • 75001 Paris •
+33 1 78 95 87 89 / +33 6 80 76 07 10 •
<https://kalstein.eu>
KALSTEIN FRANCE, S. A. S





Kalstein®

A different accompaniment, at your service

OUR SERVICES

Benefits and Support

In Kalstein France, we take care of the full satisfaction of our customers, that is why we provide value-added services of the highest level based on our experience.



Online Inductions and Trainings

In any part of the world, receive your induction or training from our specialized team of engineers



Quick Response

Our work team is always available to response all your consults or questions, in order to support you in any situation.



#Letsgivemore ♥

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



Technical Support

Enjoy of personalized advice for the correct preventive and corrective maintenance of your equipment, thanks to Kalstein's manuals and articles, special catalogues and video tutorials.



Delivery Logistics

We take care of all the necessary logistics for the dispatch of your goods, whether is by sea, land or air.



Kalstein Worldwide

With more than 25 years growing with our customers, Kalstein's multiformat and modern content, is now present in more than 10 countries and increasing.



-40°C Low Temperature Freezer Serie YR05308



YR05306



YR05308



YR05307



YR05309/ YR05311



KEY FEATURES

- Microprocessor control, adjustable temperature range: -30°C to -40°C
- LED digital display and increment at 0.1°C
- Permanently lubricated cooling fan for safety and longevity.
- Independent inner door to avoid more cooling leaking out, and provide more stable inside temperature performance
- High density CFC-Free urethane foam insulation.



ERGONOMIC DESIGN

- USB data logging and temperature recorder (optional).
- Build-in lock with safety and beauty
- Lockable caster design for customer to move as needed



RELIABILITY

- Chemically stable, CFC-free, commercially available and environmentally safe refrigerant.
- Optimized refrigeration system designed to maximize cooling effect and temperature uniformity
- Microprocessor control, digital display, adjustable temperature range: -30°C--40°C
- LED digital display for clear observation,



SAFETY

- Multiple malfunction alarms to detect high and low temperature, sensor error, power off, temperature controller malfunction, door ajar.
- Two types of alarm indications: audible buzzing and visual flashing light.
- Corrosion proof cabinet interior design
- Power failure protect: the device would be attack by the high current when all devices restart simultaneously, the start-delay function would protect device from the damage



ELECTRIC CONTROL

- Wide voltage tolerance design with applicable voltage range of 187-242V/AC



#Letsgivingmore

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved © KALSTEIN France S. A. S.,
2 Rue Jean Lantier • 75001 Paris •
+33 1 78 95 87 89 / +33 6 80 76 07 10 •
<https://kalstein.eu>
KALSTEIN FRANCE, S. A. S



-40°C Low Temperature Freezer**Serie YR05308****YR05309/ YR05311****YR05100/ YR05310****RELIABILITY**

- Single temperature control system with double door construction.
- Flexible and easy storage by height-adjustable shelf trays
- Maintains the quality of the samples during preservation
- 2 completely independent chambers with their own temperature displays

KEY FEATURES

- 2 Independent doors ,2 Compressors,2 Test Holes,2 Displays.
- Standard with thermal printer to record 1 year's data

**FEATURES**

- Height-adjustable shelf trays allow you to adjust the inside of the chambers according to the size of the samples. By changing the height of the shelf trays, the unit can accommodate various sizes of samples including stored in your conventional models.
- Door latch with provision for a padlock for extra protection of samples.
- Equipped with separate doors that suppress the leakage of cold air during opening and closing of the doors, and manual defrosting that helps avoid temperature impact on the samples.

**SAFETY DESIGN**

- To securely preserve/manage the valuable samples, in addition to a standard-feature door lock, a hole in the latch allows a padlock to be attached.
- Security functions that help protect valuable samples with a temperature control capability that inhibits the change in temperature inside the chamber, and an alarm/security function that prevents errors, the unit maintains the quality of the preserved samples.
- Temperature recorder (optional)
- Front-mounted display/control panel located at convenient height for easy access
- Insulated door with gasket for sample protection and uniformity
- 2 USB port interface

**EASY TO CLEAN**

- Top and bottom chambers are equipped with 2 independent refrigeration circuits that enables separate temperature settings and defrosting for the two chambers.
- With the capability to defrost the top and bottom chambers separately, the unit makes it easy to transfer samples during defrosting.

**#Let'sgive more**

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved © KALSTEIN France S. A. S.,
2 Rue Jean Lantier • 75001 Paris •
+33 1 78 95 87 89 / +33 6 80 76 07 10 •
<https://kalstein.eu>
KALSTEIN FRANCE, S. A. S



-40°C Low Temperature Freezer

Serie YR05308



Double LED digital display, which can separately display the temperature data and various alarm information of the upper and lower rooms



Two test holes are equipped on the right of the cabinet, installing the temperature recorder to detect the temperature change of each room

Top and bottom chambers are equipped with 2 independent refrigeration circuits that enables separate temperature settings and defrosting for the two chambers. With the capability to defrost the top and bottom chambers separately, the unit makes it easy to transfer samples during defrosting.



The freezer room is equipped with a standard aluminum alloy door handle with pressure relief function, which is convenient for frequent opening and closing in a short time



#Let'sgive more ♥


Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved © KALSTEIN France S. A. S.,
2 Rue Jean Lantier • 75001 Paris •
+33 1 78 95 87 89 / +33 6 80 76 07 10 •
<https://kalstein.eu>
KALSTEIN FRANCE, S. A. S



-40°C Low Temperature Freezer
Serie YR05308



Pull-down test at 32°C ambient

Inner 7 drawers



#Letsgivemore ♥

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved © KALSTEIN France S. A. S.,
 2 Rue Jean Lantier • 75001 Paris •
 +33 1 78 95 87 89 / +33 6 80 76 07 10 •
<https://kalstein.eu>
KALSTEIN FRANCE, S. A. S



-40°C Low Temperature Freezer

Serie YR05308



	Model	YR05306	YR05308	YR05307	YR05309	YR05310
Specifications	Shelf (drawer)	Shelves	Drawers/7	Shelves	Shelves/12 drawers	Shelves/drawers
	Cooling method	Direct cooling	Direct cooling	Direct cooling	Direct cooling	Direct cooling
	Defrost	Manual	Manual	Manual	Manual	Manual
	Refrigerant	R290	R290	R290	R290	R290
	Power consumption(kWh/24h)	3	1.5	3	/	3.4
	Noise (db)	46	46	46	49	55
	Ambient temperature (°C)	10~32°C	10~32°C	10~32°C	10~32°C	10~32°C
	Temperature range (°C)	-10~-25°C	-10~-25°C	-10~-25°C	-10~-25°C	-10~-25°C
Cooling system	Compressor brand/QTY	CUBIGELN/1	DONPERN/1	CUBIGELN/1	CUBIGEL/2	MEIZHI/2
	Sensor	NTC	NTC	NTC	NTC	NTC
	Temperature controller	Microprocessor	Microprocessor	Microprocessor	Microprocessor	Microprocessor
	Display	Digital display	Digital display	Digital display	Digital display	Digital display
Power	Voltage/frequency (V/Hz)	220/50Hz	220/50Hz	220/50Hz	220/50Hz	220/50Hz
	Power (W)	180W	180W	180W	/	260W
	Current (A)	1.4A	1.5A	1.4A	/	1.9A
Material	Inside material	Color sprayed steel	Color sprayed steel	Color sprayed steel	Color sprayed steel	Color sprayed steel
	Outside material	Color sprayed steel	Color sprayed steel	Color sprayed steel	Color sprayed steel	Color sprayed steel
	Insulation	PURF	PURF	PURF	PURF	PURF
Size	Capacity (L/cu.ft)	268/9.46	278/9.81	328/11.58	358/12.6	528/18.64
	NT/GF. (kg)	93.5/113.5	85/101	104/125	138/178	151/184
	Exterior size(W*D*H)(mm)	690*680*1635	670*640*1695	690*680*1900	720*830*1870	910*845*1875
	Interior size(W*D*H)(mm)	508*455*1137	480*415*1460	508*455*1393	466*636*625	(651*631.5*635)*2
	Package size(W*D*H)(mm)	760*760*1750	730*670*1850	750*760*2030	780*920*1990	930*970*2000
	CBM	1.01	0.90	1.16	1.43	1.80
	20GP/40GP/40HQ	21/45/45	24/51/51	21/48 /48	18/39/39	12/ 24/24
Alarm	High/low temperature	Y	Y	Y	Y	Y
	Power off	Y	/	Y	Y	Y
	Sensor malfunction	Y	Y	Y	Y	Y
	Ambient temperature (°C)	/	/	/	Y	Y
	Abnormal voltage	/	/	/	/	/
	Temperature controller malfunction	Y	Y	Y	Y	Y
	Door ajar	Y	Y	Y	Y	Y
Power failure backup system (alarm)	8H	8H	8H	8H	8H	
Accessories	Caster	Y	Y	Y	Y	Y
	Test hole	1/25MM	1/25MM	1/25MM	2/25MM	2/25MM
	USB port	/	/	/	Y	Y
	Data logger	Optional	Optional	Optional	Optional	Optional
	Remote alarm	Y	/	Y	Optional	Y
Other	Certification	ISO,CE	ISO,CE	ISO,CE	ISO	ISO,CE



#Let'sgive more

Thanks to your purchase, a donation is made to a non-profit foundation that fights against cancer and helps vulnerable communities.



All rights reserved © KALSTEIN France S. A. S.,
2 Rue Jean Lantier • 75001 Paris •
+33 1 78 95 87 89 / +33 6 80 76 07 10 •
<https://kalstein.eu>
KALSTEIN FRANCE, S.A. S





 **Kalstein**[®]
A different accompaniment, at your service

#LETSGIVEMORE 

**WITH THE
ACQUISITION
OF A KALSTEIN
EQUIPMENT**

YOU MAKE A CONTRIBUTION TO:


 **Fundación
Jacinto Convit**
<https://www.jacintoconvit.org/>

 **ONE
TREE
PLANTED**
<https://onetreepanted.org>

 **Humatem**
Solidarité et coopération
biomédicale
<https://www.humatem.org/>

 **MANIAPURE
FOUNDATION USA**
<https://www.maniapurefoundation.org/>

Articles Kalstein
(Social Networks and Official Websites)



Kalstein Blog
Not just be informed, be fully informed
The 3 articles of the week!
Read more on Kalstein's social medias or official websites
<https://kalstein.eu/articles>



1
Read this ARTICLE NOW
How does the climate affect your microscope?
A microscope is an instrument that allows observing and measuring objects at a very small scale. This is achieved through a complex system of lenses and mirrors, which form...

Kalstein Blog
Article of the week:
How does the climate affect your microscope?
Read more on Kalstein's social medias or official websites
<https://kalstein.eu/articles>




2
Read this ARTICLE NOW
What is the importance of the laboratory refrigerator?
A refrigerator is a device that is one of the most common pieces of equipment used in laboratories. It is a controlled environment (refrigerated space), various fluids and substances...

Kalstein Blog
Article of the week:
What is the importance of the laboratory refrigerator?
Read more on Kalstein's social medias or official websites
<https://kalstein.eu/articles>

Kalstein Training Videos
(Youtube Channel and Official Websites)



Kalstein France - Jacinto Convit Foundation / Alliances
23 views • 3 years ago



Kalstein's Microscopes
445 views • 1 week ago



PARIS - FRANCE
HEADQUARTER
2 Rue Jean Lantier
75001 Paris - France

Tlf: +33 (0) 01 78 95 87 89
Cel: +33 (0) 6 80 76 07 10
sales@kalstein.eu

<https://kalstein.eu/>
<https://www.kalstein.fr/>

