




Instruction Manual Model YR403-1 Kalstein Bacti-cinerator Sterilizer



All rights reserved ® KALSTEIN France S. A. S., Optimum Business Center 450 Rue Baden Powell, • 34000 Montpellier, France. Tlf: +33 467158849 / +33 680760710/ +33 663810023 https://kalstein.eu KALSTEIN FRANCE, S. A. S







Benefits and Support

In Kalstein France, we take care of the full satisfaction of our customers, that is why we provide value-added services of the highest level based on our experience.

Online Inductions and Trainings

In any part of the world, receive your induction or training from our specialized team of engineers

Quick Response Our work team is always available to response all your consults or questions, in order to support you in any situation.



Hetrs Give Worker Haris to your purchase, a donation will be made to a non-profit foundation that fights against breast cancer and helps most vulnerable communities.

Technical Support Enjoy of personalized advice for the correct preventive and corrective mainterance of your equipment, than's to Kalstein's manuals and articles, special catalogues and video tutorials.





Delivery Logistics We take care of all the necessary logistics for the dispatch of your goods, whether is by sea, land or.air.

Kalstein Worldwide With more than 25 years growing with our customers, Kalstein's multiformat and modern contert, is now present in more than 10 countries and increasing.



Foreword

Thank you for purchasing our Products: Bacti- Cinerator Sterilizer, This Manual for users contains function and operation of the Instrument. In order to use the instrument properly, please read this manualcarefully before using the Instrument.



Please check the Instrument and Appendix with thepacking list when you first open the instrument packing case. If you find there is something wrong with the Instrument and the Appendix, do contact the vendor or the producer.



Contents

1. Introduction1
1.1 Structure Description1
2. Technical data2
3. Operating Instructions
4. Precautions and Maintenance4
5. Warranty Information
6. Packing List

5 Warranty Information

5.1 The Bacti-Cinerator Sterilizer unit itself (without heater element) is warranted for one year against defects in material and workmanship. The warrantedlife of the heater Element is six months.

5.2 This warranty becomes effective when the ultimate user receives the product and will be based on proof ofpurchase or date of invoice.

5.3 Should damage to the instrument occur due to improper use or improper maintenance, this writtenwarranty is void.

6 Packing List

No.	Item	Туре	QTY
1	Bacti-Cinerator Sterilizer	YR403-1	1
2	Operations manual		1
3	Fuse	250V 3A	2
4	Certification		1



4 Precautions and Maintenance

4.1 Only insulated loop holders should be used when insertinginoculating loops or needles into the heater element.

4.2 The Bacti-Cinerator Sterilizer is not intended for use with scalpels, forceps or any sharp objects. The use of such objectscan cause element malfunction and void the heater element warranty.

4.3 Visual inspection of the heater element should be performed periodically to determine if the heater element core is worn. Inspect for small cracks and residue buildup in both the cool and heated conditions. In the heated condition, crackscan be seen as small, intensely yellow-orange fissures. If any defects are noted, the heater element should be replaced before element malfunction occurs.


4.4 The inoculating loops and needles should not be allowed toset in the heater element for extended periods of time. This willcause the loop holder to become extremely hot and increase the wearing of the loops and needles.

1 Introduction

The Bacti-Cinerator Sterilizer is a gasless ,flameless sterilizer for use with inoculating loops and needles. Sterilization is accomplished through infrared heat withoutdangerous spattering of microorganisms.

Before starting up this unit for the first time, please readthe rest of this operations manual.

1.1 Structure Description





2 Technical data

Model	YR403-1
Power supply	220 V~ 60Hz
Power	170W
Highest temperature at core	825DC D 50DC
Largest possible diameterof item to be sterilized	φ14mm
Length of heating area	150mm
Heating time	20min
Fuse	250V 3A 5X20
Ambient temperature	$5^{\circ}\mathrm{C}\sim40^{\circ}\mathrm{C}$
Dimensions (W×D×H)	97X185X185mm
Net Weight	1.1kg

3 Operating Instructions

3.1 Remove any packaging that protects the Bacti-CineratorSterilizer from being damaged during shipment.

3.2 Plug the electrical cord into the appropriate outlet. The unitmust be properly grounded.

3.3 The red indicator light will come on when the switch is in the "High" position. Twenty minutes after the Bacti-Cinerator Sterilizer is plugged in ,the optimum sterilizing temperature(825°C) will be reached. If the unit is not going to be used for extended periods of time ,please set the switch in "Off" position to conserve the life of the heater element .

<u>Note: If the unit keep the sterilizing temperature</u> (825°C) over three hours, please set the switch in "Low" position for half an hour ,then set the toggle switch in "High" position again. This will conserve the life of the heater elementtoo. The green indicator light will come on when the switch is in the "Low" position.

3.4 Gently insert the loop or needle, attached to an insulated loop holder, into the heater element. Avoid scraping the sidesof the element to ensure the longevity of your loop and heaterelement. The loop should remain within the heater element a minimum of five seconds.